



RAASI[®]
Pumps - Pipes - Cables

**M5P4
SUBMERSIBLE
PUMPS**

M5P4 SUBMERSIBLE PUMPS (V5 MOTOR TO V4 PUMP)

(Suitable for 5" & Above Dia Bore Wells)

MOTOR: SS Body, **ROTOR:** Copper Rotor,

PUMP: SS Body,

BOWL & IMPELLER: Noryl / PVC ORIGIN WITH SS NECK RING



PER STAGE: 20 FEET HEAD

MODEL	H.P	STAGE	OUT LET (50MM) 2"	DISCHARGE IN LPM						PRICE WITHOUT PANEL	
				70	95	115	135	165	185		205
M5P4RSMTT10-30	6	30	HEAD IN	165	150	135	120	90	60	30	39030
M5P4RSMTT10-37	7.5	37	METERS	205	185	166	148	111	75	37	45600

MODEL	H.P	STAGE	OUT LET (50MM) 2"	DISCHARGE IN LPM						PRICE WITHOUT PANEL	
				85	95	110	150	165	200		225
M5P4RSMTT12-24	6	24	HEAD IN	132	120	108	96	72	48	24	37625
M5P4RSMTT12-30	7.5	30	METERS	165	150	135	120	90	60	30	43930

MODEL	H.P	STAGE	OUT LET (50MM) 2"	DISCHARGE IN LPM						PRICE WITHOUT PANEL	
				175	200	250	300	330	360		415
M5P4RSMTT18-17	6	17	HEAD IN	82	77	68	60	51	34	18	41350
M5P4RSMTT18-23	7.5	23	METERS	110	104	92	81	70	45	25	49360

PER STAGE: 25 FEET HEAD

MODEL	H.P	STAGE	OUT LET (32MM) 1.25"	DISCHARGE IN LPM						PRICE WITHOUT PANEL	
				25	35	45	50	55	65		70
M5P4RSMTT2-50	5	50	HEAD IN METERS	350	325	300	275	250	200	150	40480
M5P4RSMTT2-60	6	60		420	390	360	330	300	240	180	45715
M5P4RSMTT2-70	7.5	70		490	455	420	385	350	280	210	53140

MODEL	H.P	STAGE	OUT LET (32MM) 1.25"	DISCHARGE IN LPM						PRICE WITHOUT PANEL	
				50	65	75	85	95	115		130
M5P4RSMTT5-29	5	29	HEAD IN METERS	203	190	175	160	145	116	88	36810
M5P4RSMTT5-35	6	35		245	230	210	195	175	140	105	41310
M5P4RSMTT5-43	7.5	43		301	280	260	240	215	172	130	48140

MODEL	H.P	STAGE	OUT LET (40MM) 1.5"	DISCHARGE IN LPM						PRICE WITHOUT PANEL	
				60	70	85	95	100	125		145
M5P4RSMTT7-25	5	25	HEAD IN METERS	175	165	150	140	125	100	75	35950
M5P4RSMTT7-31	6	31		218	205	185	170	155	125	95	40410
M5P4RSMTT7-40	7.5	40		280	260	240	220	200	160	120	47450

NOTE: Above performance may varied on field conditions, bore well yield, bore well depth,
Cable selection & power fluctuations

